




BGAN terminals

A quick reference guide









• Inmarsat's Broadband Global Area Network service – BGAN – is accessible via a small, lightweight, satellite terminal, which is quick to set up and easy to use. And you can use the same device worldwide.

A range of terminals is available – land portable, vehicular and military systems – providing performance options to suit different operational needs. The service is accessed via Inmarsat LaunchPad, a software interface, which is standard across all terminals.

	Land portable					Military	
							
	Wideye™ Sabre™ I¹ Voice and data, single-user device	EXPLORER® 300 Highly compact, robust device	EXPLORER® 500 High bandwidth, highly portable device	HUGHES 9201¹ High performance, multi-user device	EXPLORER® 700 Multi-user device with extensive functionality	RF-7800B-DU024 Rugged, land portable high performance system	RF-7800B-VU104 Rugged, vehicular high performance system
Manufacturer	Addvalue Communications www.wideye.com.sg	Thrane & Thrane www.thrane.com	Thrane & Thrane www.thrane.com	Hughes Network Systems www.hughes.com	Thrane & Thrane www.thrane.com	Harris Corporation www.harris.com	Harris Corporation www.harris.com
Size	259 x 195mm (1.6kgs)	217 x 168mm (1.4kgs)	217 x 218mm (1.4kgs)	345 x 275mm (2.8kgs)	399 x 297mm (3.2kgs)	240 x 240mm (2.8kgs)	Integrated antenna and terminal: 510 x 200mm (12.6kgs)
Standard IP	Up to 240/384kbps (send/receive)	Up to 240/384kbps (send/receive)	Up to 448/464kbps (send/receive)	Up to 492kbps (send & receive)	Up to 492kbps (send & receive)	Up to 448 / 464kbps (send/receive)	Up to 492kbps (send & receive)
Streaming IP (send & receive)	32, 64kbps	32, 64kbps	32, 64, 128kbps	32, 64, 128, 176, 256kbps, BGAN X-Stream™	32, 64, 128, 176, 256kbps, BGAN X-Stream™	32, 64, 128kbps	32, 64, 128, 256kbps ²
Voice	Via RJ-11 or Bluetooth handset / headset	Via RJ-11 or Bluetooth handset / headset	Via RJ-11 or Bluetooth handset or 3.1kHz audio / fax	Via RJ-45 ISDN handset, via ISDN TA with two RJ-11 ports for voice or 3.1kHz for audio / fax	Via RJ-11 (x2), Bluetooth handset or 3.1kHz audio / fax	Via military standard connector for normal voice, ISDN standard voice and 3.1 kHz for audio / fax	Via military standard connector for normal voice, ISDN standard voice and 3.1kHz for audio / fax
ISDN	N/A	N/A	64kbps via USB	64kbps via RJ-45	64kbps via RJ-45	64kbps via RJ-45	Data / voice: 64kbps via RJ-45
Other data interfaces	Ethernet, Bluetooth	Ethernet, Bluetooth	Ethernet, USB, Bluetooth	Ethernet, USB, WLAN 802.11b	2 x Ethernet, USB, WLAN 802.11 a/b/g, Digital I/O, Bluetooth,	Ethernet, USB via military standard connector	Ethernet, USB via military standard connector
Ingress protection	IP 54	IP 54	IP 54	IP 55	IP 52 (terminal) IP 66 (antenna)	MIL-STD-810F IP 67	MIL-STD-810F IP 67

Vehicular

						
	EXPLORER® 325 Compact, lightweight, robust system	HUGHES 9450 Highly compact, high performance system	GLOCOM GX11 Highly compact, high performance system	EXPLORER® 727 Multi-user device with extensive functionality	HUGHES 9350 Multi-user device with wireless capability	GLOCOM GX10 Multi-user device with wireless capability
Manufacturer	Thrane & Thrane www.thrane.com	Hughes Network Systems www.hughes.com	Glocom www.glocom-us.com	Thrane & Thrane www.thrane.com	Hughes Network Systems www.hughes.com	Glocom www.glocom-us.com
Size	Terminal 231 x 278mm (2.4kgs) Antenna 350 x 1200mm (4.5kgs)	Terminal 234 x 281mm (2.3kgs) Antenna 252 x 119mm (2kgs)	Terminal 260 x 210mm (2.4kgs) Antenna 276 x 150mm (1.86kgs)	Terminal 247 x 270mm (2.5kgs) Antenna 477 x 160mm (6kgs)	Terminal 260 x 256mm (2.8kgs) Antenna 477 x 153mm (5.5kgs)	Terminal 260 x 256mm (2.8kgs) Antenna 477 x 153mm (5.5kgs)
Standard IP	Up to 448 / 464kbps (send / receive)	Up to 448 / 464kbps (send / receive)	Up to 407kbps (send & receive)	Up to 492kbps (send & receive)	Up to 492kbps (send & receive)	Up to 492kbps (send & receive)
Streaming IP (send & receive)	32, 64, 128kbps	32, 64, 128kbps	32, 64, 128kbps	32, 64, 128, 256kbps ²	32, 64, 128, 256kbps ²	32, 64, 128, 256kbps ²
Voice	VoIP handset 1 Independent RJ-11 port (2-wire connector)	Via RJ-45 ISDN handset, via ISDN TA with two RJ-11 ports for voice or 3.1kHz for audio / fax	Via RJ-45 ISDN handset, via ISDN TA with two RJ-11 ports for voice or 3.1kHz for audio / fax	2 x 2-wire, RJ-11 phone / fax, 3.1kHz audio / fax	Via RJ-45 ISDN handset, via ISDN TA with two RJ-11 ports for voice or 3.1kHz for audio / fax	Via RJ-45 ISDN handset, via ISDN TA with two RJ-11 ports for voice or 3.1kHz for audio / fax
ISDN	N/A	56 / 64kbps ³	56 / 64kbps ³	56 / 64kbps ⁴	56 / 64kbps ⁴	56 / 64kbps ⁴
Other data Interfaces	2 x Ethernet	4 x Ethernet, WLAN 802.11b with extended standard connector	Ethernet, WLAN 802.11b with extended standard connector, USB	4 x Ethernet, USB	Ethernet, WLAN 802.11b with extended standard connector, USB	Ethernet, WLAN 802.11b, USB
Ingress protection	IP 31 (terminal), IP 56 (antenna)	IP 54 (terminal), IP 56 (antenna)	IP 54 (terminal), IP 56 (antenna)	IP 31 (terminal), IP 56 (antenna)	IP 54 (terminal), IP 56 (antenna)	IP 54 (terminal), IP 56 (antenna)

¹ There are derivatives of these terminals available that have been specifically designed for machine-to-machine or bespoke applications.

² Inmarsat supports 256kbps streaming at elevations above 45 degrees. Below this elevation, the 128kbps streaming connection is recommended.

³ Depending on location. Inmarsat supports ISDN at elevations above 45 degrees.

⁴ Depending on location. Inmarsat supports ISDN at elevations above 20 degrees.

How to buy BGAN

BGAN is available through Inmarsat distribution partners and service providers in more than 190 countries. Visit our website to find the right partner for your organisation.

inmarsat.com/bgant

Whilst the above information has been prepared by Inmarsat in good faith, and all reasonable efforts have been made to ensure its accuracy, Inmarsat makes no warranty or representation as to the accuracy, completeness or fitness for purpose or use of the information. Inmarsat shall not be liable for any loss or damage of any kind, including indirect or consequential loss, arising from use of the information and all warranties and conditions, whether express or implied by statute, common law or otherwise, are hereby excluded to the extent permitted by English law. INMARSAT is a trademark of the International Mobile Satellite Organisation, Inmarsat LOGO is a trademark of Inmarsat (IP) Company Limited. Both trademarks are licensed to Inmarsat Global Limited. © Inmarsat Global Limited 2011. All rights reserved. BGAN terminals March 2011.